

NANE

2-Tool Nano Soldering Station

This Plug & Play Guide corresponds to the following references:

Ref.

NANE-9D (100 V)
NANE-1D (120 V)
NANE-2D (230 V)

Information

Web page of the latest
product version



Video Guide

Watch the
product video



Packing List

The following items are included according purchased station reference:



2-Tool Nano Control Unit 1 unit

Ref. NAE-9C (100 V)

Ref. NAE-1C (120 V)

Ref. NAE-2C (230 V)

Nano Handle 2 units

Ref. NT115-A



Ref. 0020952 includes:

Ref. C115101 (1x)

C115103 (1x)

C115107 (1x)

C115112 (1x)



Ref. 0020953 includes:

Ref. C115105 (2x)

C115113 (2x)

Cartridge

Dispenser Case 2 units

Ref. 0020952 (1x) / Ref. 0020953 (1x)



High-Precision Tweezers with ESD Epoxy Coating,


Sharp Tip and Short Body 1 unit

Ref. HPTE-0C9SA

Installation

NAE

2-Tool Nano Control Unit




Power Cord

Supplied in NAE Control Unit



Installation



Specifications

NANE

2-Tool Nano Rework Station

Ref. **NANE-9D** (100 V) 50/60 Hz. Input fuse: 0.5 A. Output: 8.5 V.

Ref. **NANE-1D** (120 V) 50/60 Hz. Input fuse: 0.5 A. Output: 8.5 V.

Ref. **NANE-2D** (230 V) 50/60 Hz. Input fuse: 0.2 A. Output: 8.5 V.

- Package Dimensions / Weight:
(L x H x W) 240 x 295 x 305 mm / 4.30 kg
9.45 x 11.61 x 12.01 in / 9.48 lb

Complies with CE standards.
ESD safe.

JBC

Warranty

Information regarding the warranty of each product can be found on the final page of its instruction manual.



This product should not be thrown in the garbage.

In accordance with the European directive 2012/19/EU, electronic equipment at the end of its life must be collected and returned to an authorized recycling facility.